

WAAS CH 72823 W36A	APP CRS 359°	Rwy Idg TDZE 1115 Apt Elev 1115	4001
--	------------------------	---	-------------

RNAV (GPS) RWY 36


OSCEOLA MUNI (I75)

⚠

When VGSI inop, Circling Rwy 18 NA at night. Baro-VNAV NA when using Chariton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Chariton altimeter setting. When local altimeter setting not received, use Chariton altimeter setting and increase all DA 44 feet and all MDA 60 feet. Increase LPV all Cats visibility to 1 mile and LNAV/VNAV all Cats visibility to 1¼ mile. Visibility reduction by helicopters NA.

MISSED APPROACH:
Climb to 3000 direct JAXWU and hold.

AWOS-3 120.975	DES MOINES APP CON 123.9 360.7	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).		3000 JAXWU	
GP 3.00° TCH 40		*1780		*1.2 NM to RW36	
CATEGORY		A		B	
LPV DA		1365-7/8		250 (300-7/8)	
LNAV/VNAV DA		1423-1		308 (400-1)	
LNAV MDA		1540-1		425 (500-1)	
CIRCLING		1580-1		465 (500-1)	