

WAAS CH 90521 W24A	APP CRS 241°	Rwy Idg TDZE Apt Elev	4400 1073 1073
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24


RICHARD B HELGESON (TWM)

RNP APCH.

Baro-VNAV NA and VDP NA when using Duluth Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Duluth Intl altimeter setting: increase LPV and LNAV/VNAV DA to 1424 feet and visibility all Cats ¼ SM; increase all MDA 120 feet. Rwy 24 helicopter visibility reduction below ¾ SM NA. Circling to Rwy 15, 33 NA.

MISSED APPROACH:
Climb to 3600 direct GIBEY and on track 284° to FOSUP and hold.

AWOS-3PT 119.325	DULUTH APP CON 125.45 233.7	GCO 121.725	CTAF 122.9 0
----------------------------	---------------------------------------	-----------------------	------------------------



ELEV 1073	TDZE 1073
-----------	-----------

3600
↑
GIBEY
tr 284°

FOSUP
△

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 27).

4 NM
Holding Pattern

WARIL

061°
241°
3000

GP 3.00°
TCH 40

*LNAV only

WIPAD
1.8 NM to RW24

*0.9 NM to RW24

ANATE

2700

1680*

0.9 NM
0.9 NM
3.2 NM
6.2 NM

4400 X 75

241°

2881 X 120

1.332 UP 15

MIRL Rwy 6-24 0

REIL Rwy 6 and 24 0

CATEGORY	A	B	C	D
LPV DA	1323-7/8 250 (300-7/8)		NA	
LNAV/VNAV DA	1323-7/8 250 (300-7/8)		NA	
LNAV MDA	1380-1 307 (400-1)		NA	
CIRCLING	1600-1 527 (600-1)	1760-1 687 (700-1)		NA