

WAAS
CH **40304**
W09A

APP CRS
088°

Rwy Ldg
TDZE
Apt Elev
5074
894
895

RNAV (GPS) RWY 9

MENOMONIE MUNI/SCORE FLD (LUM)

RNP APCH.

▼

▲

Circling Rwy 18, 36 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

AWOS-3PT
118.025

MINNEAPOLIS CENTER
125.3 335.6

UNICOM
123.075 (CTAF) 0

Procedure NA for arrivals at BITLR on V510 northwest bound and V413 westbound.

(IAF) BITLR

2800 NoPT
087° (7.2)

088°

268°

4 NM

HOLD
6000
2800

2800 NoPT
044°
(10.2)

(IAF) ELPAS

IF/IAF HATEL

2800
(6)

(FAF) ANILE

WIBAM
2.2 NM
to RW09

RW09
1099±

4 NM

040°
220°

GAGNR

MSA RW09 25 NM

3200

Procedure NA for arrivals at ELPAS on V26 southwest bound.

4 NM Holding Pattern

HATEL

ANILE

WIBAM
2.2 NM
to RW09

2800

2800

*1.3 NM
to RW09

*1640

RW09

6000
2800
GP 3.00°
TCH 48

268°
088°

088°

2800

6 NM

3.6 NM

0.9

1.3

1400

2800

GAGNR

*LNAV only

81

3470 X 75

5074 X 75

36

27

CATEGORY	A	B	C	D
LPV DA		1144-3/4	250 (300-1)	NA
LNAV/VNAV DA		1423-1 1/2	529 (600-1 1/2)	NA
LNAV MDA	1360-1	466 (500-1)	1360-1 3/8 466 (500-1 3/8)	NA
CIRCLING	1420-1 525 (600-1)	1800-1 1/4 905 (1000-1 1/4)	1820-2 3/4 925 (1000-1 3/4)	NA

REIL Rwy 9 and 27 0
MIRL Rwy 9-27 and 18-36 0

MENOMONIE, WISCONSIN

MENOMONIE MUNI/SCORE FLD (LUM)

Amdt 1 20JUN19

44°54'N-91°52'W

RNAV (GPS) RWY 9