

|                                        |                        |                             |                                           |
|----------------------------------------|------------------------|-----------------------------|-------------------------------------------|
| WAAS<br>CH <b>42833</b><br><b>W20A</b> | APP CRS<br><b>201°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>6307</b><br><b>4970</b><br><b>4970</b> |
|----------------------------------------|------------------------|-----------------------------|-------------------------------------------|

RNAV (GPS) RWY 20

CLAYTON MUNI AIRPARK (CAO)

**⚠** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Circling NA west of Rwy 2-20. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Dalhart altimeter setting and increase all DA 227 feet and all MDA 240 feet, increase LPV all Cats visibility  $\frac{7}{8}$  mile, increase LNAV/VNAV all Cats visibility  $\frac{3}{4}$  mile, increase LNAV Cat C visibility  $\frac{5}{8}$  mile, and increase circling Cat C visibility  $\frac{1}{4}$  mile. Baro-VNAV and VDP NA when using Dalhart altimeter setting.

**MISSED APPROACH:** Climb to 8000 direct CACAV and hold, continue climb-in-hold to 8000.

|                        |                                             |                                 |
|------------------------|---------------------------------------------|---------------------------------|
| ASOS<br><b>120.625</b> | ALBUQUERQUE CENTER<br><b>127.85 285.475</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|------------------------|---------------------------------------------|---------------------------------|

