

|                                        |                        |                                                              |
|----------------------------------------|------------------------|--------------------------------------------------------------|
| WAAS<br>CH <b>63017</b><br><b>W16A</b> | APP CRS<br><b>162°</b> | Rwy Ldg <b>10000</b><br>TDZE <b>69</b><br>Apt Elev <b>69</b> |
|----------------------------------------|------------------------|--------------------------------------------------------------|

RNAV (GPS) RWY 16

NORTHWEST FLORIDA BEACHES INTL (ECP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Destin altimeter setting and increase all DA 88 feet, increase all MDA 100 feet, and increase LNAV/VNAV all Cats visibility and LNAV Cat C and D visibility 3⁄8 mile. Baro-VNAV and VDP NA when using Destin altimeter setting. For inop MALSR, increase LNAV Cat C and D visibility to 1 mile. For inop MALSR when using Destin altimeter setting, increase all LPV visibility to 7⁄8 mile, increase all LNAV/VNAV visibility to 1 3⁄8 mile, and increase LNAV Cat C and D visibility to 1 3⁄8 mile.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 4000 direct SCARE and hold, continue climb-in-hold to 4000.

|                        |                                  |                                              |                          |
|------------------------|----------------------------------|----------------------------------------------|--------------------------|
| ATIS<br><b>119.975</b> | TYNDALL APP CON★<br><b>125.2</b> | PANAMA CITY TOWER★<br><b>118.95 (CTAF) 0</b> | GND CON<br><b>121.65</b> |
|------------------------|----------------------------------|----------------------------------------------|--------------------------|

4 NM Holding Pattern

3000

342°

162°

GP 3.00° TCH 55

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

OTTOE

LIVVY

SIKDE 1.7 NM to RW16

RW16

SCARE

500

4000

SCARE

\*LNAV only.

\*1 NM to RW16

\*660

6 NM

4.2 NM

0.7 NM

1 NM

|              |         |               |                 |               |
|--------------|---------|---------------|-----------------|---------------|
| CATEGORY     | A       | B             | C               | D             |
| LPV DA       |         | 269-1⁄2       | 200 (200-1⁄2)   |               |
| LNAV/VNAV DA |         | 478-7⁄8       | 409 (500-7⁄8)   |               |
| LNAV MDA     | 440-1⁄2 | 371 (400-1⁄2) | 440-5⁄8         | 371 (400-5⁄8) |
| CIRCLING     | 520-1   | 451 (500-1)   | 520-1 1⁄2       | 620-2         |
|              |         |               | 451 (500-1 1⁄2) | 551 (600-2)   |

ELEV 69

TDZE 69

162°

91

1000 X 150

TWR★

3A

TDZ/CL Rwy 16 0

HIRL Rwy 16-34 0

REIL Rwy 34 0

PANAMA CITY, FLORIDA  
Amdt 2A 29MAY14

30°22'N-85°48'W

NORTHWEST FLORIDA BEACHES INTL (ECP)  
RNAV (GPS) RWY 16