

WAAS CH 40141 W30A	APP CRS 307°	Rwy Idg 3600 TDZE 1540 Apt Elev 1545
--	------------------------	---

RNAV (GPS) RWY 30



WESSINGTON SPRINGS (4X4)

NA

DME/DME RNP-0.3 NA. VDP NA when using Mitchell Muni altimeter setting. When local altimeter setting not received use Mitchell altimeter setting: increase all MDAs 100 feet and LNAV visibility Cat C ¼ SM, LP visibility Cat C ¼ SM, Circling visibility Cat B ¼ SM.

MISSED APPROACH: Climb to 4000 direct YUBUV and hold.

MINNEAPOLIS CENTER 126.25 339.8	CTAF 122.90
---	-----------------------



4000	YUBUV	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 25).			ZIGRU	4 NM Holding Pattern
		1 NM to RW30		3.00° TCH 40	3200	127°/307°
		1 NM	4.1 NM	6 NM		
CATEGORY	A	B	C	D		
LP MDA	1880-1 340 (400-1)				NA	
LNAV MDA	1940-1 400 (400-1)		1940-1 400 (400-1)		NA	
CIRCLING	2180-1 635 (700-1)	2340-1 795 (800-1)	2720-3 1175 (1200-3)		NA	