

WAAS CH 87137 W31B	APP CRS 306°	Rwy Ldg 2755 TDZE 160 Apt Elev 162
--	------------------------	---

RNAV (GPS) RWY 31

SOUTH NAKNEK NR 2 (WSN)(PFWS)

RNP APCH.

▼ Baro-VNAV and VDP NA when using King Salmon altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use King Salmon altimeter setting and increase all DA/MDA 40 feet. Circling Rwy 5 NA at night.

MISSED APPROACH:
Climb to 700 then climbing left turn to 3200 direct TIKGU and hold.

AWOS-3P
121.575

ANCHORAGE CENTER
124.8 354.0

CTAF
122.9 0

MISSED APCH FIX
TIKGU

ELEV 162

TDZE 160

700

3200

TIKGU

*LNAV only.

*1.6 NM to RW31

4 NM Holding Pattern

GP 3.00°

TCH 35

CATEGORY	A	B	C	D
LPV DA	410-1	250 (300-1)	NA	
LNAV/VNAV DA	410-1	250 (300-1)	NA	
LNAV MDA	700-1	540 (600-1)	NA	
CIRCLING	700-1	538 (600-1)	NA	