

APP CRS
038°

Rwy Ldg
TDZE
3607

Apt Elev
3607

RNAV (RNP) Z RWY 4

RICK HUSBAND AMARILLO INTL (AMA)

For uncompensated Baro-VNAV systems, procedure NA below -14°C (7°F) or above 53°C (128°F).
RF required. GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM.

MALSR

MISSED APPROACH: (Do not exceed 185K until MAWGO)
Climb to 5400 on track 038° to KILTE, right turn to MAWGO, then track 157° to CAUDE and hold.

ATIS 118.85 350.3	AMARILLO APP CON★ 119.5 307.0	AMARILLO TOWER★ 118.3(CTAF) 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95
-----------------------------	---	---	-------------------------------	-----------------------------------	-------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 61).

5400
tr 038°

MAWGO

CAUDE

See planview for multiple IF locations.

GP 3.00°
TCH 44

4600

038°

3 NM

RW04

CATEGORY	A	B	C	D
RNP 0.12 DA		3969/40	362 (400-¾)	
RNP 0.30 DA		4019/50	412 (500-1)	

AUTHORIZATION REQUIRED

REIL Rwy 13
HIRL Rwy 4-22 and 13-31

ELEV 3607 TDZE 3607

SC-2, 30 OCT 2025 to 27 NOV 2025

SC-2, 30 OCT 2025 to 27 NOV 2025

AMARILLO, TEXAS
Amdt 1 12OCT17

35°13'N-101°42'W

RICK HUSBAND AMARILLO INTL (AMA)
RNAV (RNP) Z RWY 4