

WAAS
CH **78318**
W36A

APP CRS
001°

Rwy ldg **11602**
TDZE **254**
Apt Elev **254**

RNAV (GPS) RWY 36

ARKANSAS INTL (BYH)

▼

NA

Inop table does not apply. Baro-VNAV NA when using Blytheville Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Circling NA east of Rwy 18-36. DME/DME RNP-0.3 NA. Obtain local altimeter setting on CTAF; when not received, use Blytheville Muni altimeter setting and increase all DA 14 feet and all MDA 20 feet. Increase LNAV/VNAV all Cats and LNAV Cat C/D visibility ½ mile.

MISSED APPROACH: Climb to 2500 direct CEDVA and hold.

MEMPHIS CENTER
134.65 316.15

UNICOM
122.7 (CTAF) 0

290

△ 511

444 △

TETOE

1.4 NM to RW36

595 △

△ 459

354±

△ 745

(FAF)

GENRE

(IF/IAF)

HABSI

2000

001°

(6)

181°

001°

6 NM

MISSED APCH FIX

6 NM

181°

001°

CEDVA

30 NM to HABSI

2500

HABSI

091°

271°

30 NM to HABSI (NoPT)

2500

6 NM Holding Pattern

HABSI

2500

181°

001°

GP 3.00° TCH 51

GENRE

2000

TETOE 1.4 NM to RW36

*740

RW36

2500 CEDVA

*LNAV only.

CATEGORY	A	B	C	D
LPV DA		454-¾	200 (200-¾)	
LNAV/VNAV DA		537-1	283 (300-1)	
LNAV MDA		620-1	366 (400-1)	
CIRCLING	700-1 446 (500-1)	720-1 466 (500-1)	800-1½ 546 (600-1½)	820-2 566 (600-2)

389 ☆

81

11602 X 150

36

001° to RW36

HIRL Rwy 18-36 0

BLYTHEVILLE, ARKANSAS

Amcl 3 11DEC14

ARKANSAS INTL (BYH)

35°58' N-89°57' W

RNAV (GPS) RWY 36