

LOC/DME I-AHI	APP CRS	Rwy Ldg
109.1	352°	13500
Chan 28		TDZE 6118
		Apt Elev 6187

ILS or LOC RWY 35R

CITY OF COLORADO SPRINGS MUNI (COS)


⚠

RADAR required when R-2601 in use.


MISSED APPROACH:

Climb to 6700 then climbing right turn to 9000 on heading 047° and on BRK VOR/DME R-091 to ADANE INT/BRK 11.1 DME and hold.

ATIS	SPRINGS APP CON	SPRINGS TOWER	GND CON	CLNC DEL
125.0 254.3	124.0 257.875	119.9 360.6	121.7 348.6	134.45 363.125



ELEV 6187	D	TDZE 6118
MIRL Rwy 13-31		
HIRL Rws 17R-35L and 17L-35R		
REIL Rws 13, 17R, 31 and 35R		
TDZ/CL Rws 17L and 35R		



Procedure NA for arrival on
PUB VORTAC airway radials
267 CW 354.

IAF
PUEBLO
116.7 PUB
Chan 114

ALTERNATE
MISSSED
APCH FIX

R-245
PUB
116.7
Chan 114

R-354
DRAKE
PUB
18.7

112.1 HGO
Chan 58

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).			6700	9000	BRK R-091	ADANE △
FALUR INT I-AHI 12.5			CEGIX INT I-AHI 5.9		hdg 047°	
8100			8100		I-AHI DME ANTENNA *LOC only	
GS 3.00° TCH 55			Use I-AHI DME when on the localizer course.		*I-AHI 0.6	
6.6 NM			5.3 NM		0.8 NM	
CATEGORY	A	B	C	D		
S-ILS 35R	6318/40			200 (200-¾)		
S-LOC 35R	6420/55	302 (300-1)	6420/45	302 (300-¾)		
CIRCLING	6740-1 553 (600-1)	6800-1 613 (700-1)	7040-2½ 853 (900-2½)	7260-3 1073 (1100-3)		