

RNAV (GPS) RWY 35R
SOUTH TEXAS RGNL AT HONDO (HDO)

▼ Baro-VNAV NA when using Castroville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). Visibility reduction by helicopters NA. When local altimeter setting not received, use Castroville altimeter setting and increase all DA 62 feet and all MDA 80 feet, increase LNAV/VNAV all Cats, and LNAV and Circling Cats C and D visibility ¼ mile. Circling Rwy 8, 13, 17R, 26, 31, 35L NA at night.

MISSED APPROACH:
Climb to 3700 direct
JENDE and hold.

Procedure NA for arrival on SAT
VORTAC airway radials 175 CW 190.

MISSED APCH FIX

4 NM

172°

352°

JENDE

1448

1220

1026

RW35R

1136

999±

ZOMSU
1.7 NM to RW35R

(FAF)
HOHME

2600

352°

(6.1)

(IF/IAF)
MUNJO

3500 NoPT

262°

(5)

(IAF)
KUXUJ

172°

352°

4 NM

SAN ANTONIO
SAT

4000

220°

(43.2)

MSA RW35R 25 NM

4100

ELEV 930

TDZE 917

HONDO, TEXAS
Orig-B 15JUL21