


WAAS CH 90411 W04A	APP CRS 046°	Rwy Ldg 7976 TDZE 258 Apt Elev 266
--	------------------------	---

RNAV (GPS) RWY 4L

BILL AND HILLARY CLINTON NTL/ADAMS FLD (LIT)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 4L helicopter visibility reduction below ¾ SM NA. For inop ALS, increase LNAV Cat A and B visibility to RVR 5000. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.	MALSR 	MISSED APPROACH: Climb to 2900 direct ODXIH and on track 052° to BRAUM and hold.
--	--	--

D-ATIS 125.65	LITTLE ROCK APP CON 135.4 353.6	ADAMS TOWER 118.7 257.8	GND CON 121.9 339.8	CLNC DEL 118.95
-------------------------	---	-----------------------------------	-------------------------------	---------------------------



ELEV 266		D TDZE 258	
4 NM Holding Pattern		VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 50).	
2900 ← 226° → 046°		2900 ODXIH tr 052° BRAUM	
GP 3.00° TCH 46		*LNAV only.	
2000		*960	
6.1 NM		3.2 NM	
0.6 NM		1.5 NM	
CATEGORY	A	B	C
LPV DA	544/40	286 (300-¾)	
LNAV/VNAV DA	824-1½	566 (600-1½)	
LNAV MDA	780/40	522 (600-¾)	780/55 522 (600-1)
CIRCLING	820-1 554 (600-1)	1000-1 734 (800-1)	1180-2¾ 914 (1000-2¾) 1180-3 914 (1000-3)