


LOC I-LKS 109.1	APP CRS 297°	Rwy Idg 7250 TDZE 480 Apt Elev 501
---------------------------	------------------------	---

LOC RWY 29


LOUISVILLE MUHAMMAD ALI INTL (SDF')

RADAR required. ADF or DME required.		MALSR 	MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 heading 268° and on IIU VORTAC R-279 to DAMEN and hold.
Circling Rwy 11 NA at night. Rwy 29 helicopter visibility reduction below RVR 4000 NA. For inop ALS, increase S-29 visibility Cats A/B to RVR 5500 and Cats C/D to 1½ SM.			


D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
--------------------------	--	--	-------------------------------	--------------------------------	-------



ELEV 501	D	TDZE 480
----------	---	----------



1100	4000	IIU R-279	DAMEN	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 56).
hdg 268°				LAANG LK LOM
				One Minute Holding Pattern



CATEGORY	A	B	C	D
S-29	1060/40	580 (600-¾)	1060-1¼	580 (600-1¼)
CIRCLING	1060-1 559 (600-1)	1140-1 639 (700-1)	1160-1¾ 659 (700-1¾)	1400-3 899 (900-3)

SE-1, 30 OCT 2025 to 27 NOV 2025

SE-1, 30 OCT 2025 to 27 NOV 2025