

APP CRS
180°

Rwy Idg
TDZE
Apt Elev

11120
290
341

RNAV (RNP) Y RWY 18C

MEMPHIS INTL (MEM)

For uncompensated Baro-VNAV systems, procedure NA below -10°C (14°F) or above 54°C (130°F). GPS required. For inop ALs, increase RNP 0.30* all Cats visibility to 1½ SM and RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations.

MALSR


MISSED APPROACH: Climb to 5000 on track 180° to CEDEN on track 137° to KEEZE and hold, continue climb-in-hold to 5000. *Missed approach requires a minimum climb of 400 feet per NM to 1000.

MEMPHIS APP CON	MEMPHIS TOWER	GND CON
119.1 291.6 (176°-355°)	(Rwy 9-27) 118.3 257.8	(Rwy 9-27) 121.0 379.2
125.8 338.3 (356°-175°)	(Rwys 18C-36C, 18L-36R) 119.7 257.8	(Rwys 18C-36C, 18L-36R) 121.9 379.2
	(Rwy 18R-36L) 128.425 257.8	(Rwy 18R-36L) 121.65 379.2

D-ATIS
127.75

CLNC DEL
125.2

CPDLC



ELEV 341

TDZE 290

180°

5000

tr 180°

CEDEN

tr 137°

KEEZE

LAURI

3900

JALDO

2000

RW18C

5.2 NM

6.1 NM

GP 3.00°

TCH 54

TDZ/CL Rwys 18L, 18C, 18R, 36R, 36C, and 36L

HIRL all Rwys

CATEGORY	A	B	C	D
RNP 0.30 DA*	655/35	365 (400-%)		
RNP 0.30 DA	747/54	457 (500-1)		

AUTHORIZATION REQUIRED