

APP CRS
117°

Rwy Ldg
TDZE
Apt Elev

9501
3200
3206

RNAV (RNP) Z RWY 12
MISSOULA MONTANA (MISO)

RNP AR APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21° C (-6°F) or above 43°C (109°F).

For inop ALS, increase RNP 0.12 all Cats visibility to RVR 6000. For inop ALS, increase RNP 0.30 all Cats visibility to 2½ SM.

When local weather not received, procedure NA.

MALSRL

MISSED APPROACH: Climb to 13000 on track 117° to OKASE and on track 123° to TAGOE and hold, continue climb-in-hold to 13000.

*Missed approach requires minimum climb of 350 feet per NM to 8300; if unable to meet climb gradient, see RNAV (GPS) Y RWY 12.

#Missed approach requires minimum climb of 425 feet per NM to 8300.

ATIS
126.65

SPOKANE APP CON*
124.9 298.95

MISSOULA TOWER*
118.4 (CTAF) 0 377.175

GND CON
121.9

UNICOM
122.95

MULLAN PASS
MLP

Procedure NA on arrivals at MLP VOR/DME on V120 westbound and V2 northwestbound.

10000
096°
(45.2)

MSA RW12 25 NM
11100

(IAF) NABNE

8600
124°
(9.4)

(IF) FERSI

6500
108°
(6.8)

SUCTO

4000

(FAF) WENKE

5600
117° (3.2)

3323
RW12

117°
(6.2)

(IAF) JUMIS
(RF REQD)

10000
265°
(17)

LOLLO

10000
265°
(17)

Procedure NA for arrivals at LOLLO on V187 eastbound.

MISSED APCH FIX

OKASE

123°
(6.5)

TAGOE

120°
300°
(not to scale)

8 NM

ELEV 3206 D TDZE 3200

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).

FERSI

SUCTO

WENKE

RW12

GP 3.00°
TCH 45

8600

108°

6500

117°

5600

13000

OKASE

tr 117°

tr 123°

TAGOE

117°

TWR

9501 X 150

30

CATEGORY

A

B

C

D

RNP 0.12 DA#

3518/40

318 (400-¾)

RNP 0.30 DA*

3880-2

680 (700-2)

AUTHORIZATION REQUIRED

REIL Rwy 30
MIRL Rwy 8-26
HIRL Rwy 12-30

MISSOULA, MONTANA

Orig-D 24MAY18

46°55'N-114°05'W

MISSOULA MONTANA (MISO)
RNAV (RNP) Z RWY 12

NW-1, 30 OCT 2025 to 27 NOV 2025

NW-1, 30 OCT 2025 to 27 NOV 2025