



LOC I-MSL 109.7	APP CRS 297°	Rwy Idg TDZE Apt Elev	6694 551 551
---------------------------	------------------------	-----------------------------	---

ILS Z or LOC Z RWY 30
NORTHWEST ALABAMA RGNL (MSL)

DME required. RADAR required.	MALSR 	MISSED APPROACH: Climb to 1200 then climbing right turn to 3000 on heading 020° to intercept RQZ VORTAC R-268 to JOBUM/RQZ VORTAC 42.5 DME/RADAR and hold, continue climb-in-hold to 3000.
DME from MSL DME. Simultaneous reception of I-MSL and MSL DME required. For inop ALS increase S-LOC 30 Cats C/D visibility to 1 SM.		

ASOS 119.425	MEMPHIS CENTER 120.8 307.0	GCO 121.725	UNICOM 123.05 (CTAF) 0
------------------------	--------------------------------------	-----------------------	----------------------------------



1200	3000	RQZ R-268	JOBUM RQZ 42.5 RADAR	MSL DME	HUPEK MSL 7 RADAR	One Minute Holding Pattern
		DIXLI MSL 3.1	TICVU MSL 0.4 RADAR	2300	297°	117°
1400		MSL 4.6	MSL 5.6	2300	297°	5000 2700
1 NM		1.5 NM	2.8 NM	7.3 NM		
CATEGORY	A		B	C	D	
S-ILS 30	751-1/2		200 (200-1/2)			
S-LOC 30	920-1/2 369 (400-1/2)		920-5/8 369 (400-5/8)			
CIRCLING	1040-1 489 (500-1)		1280-2 729 (800-2)		1280-2 1/4 729 (800-2 1/4)	

SE-4, 30 OCT 2025 to 27 NOV 2025

SE-4, 30 OCT 2025 to 27 NOV 2025