RNAV (GPS) RWY 18

MYRTLE BEACH INTL (MYR)

WAAS CH 93819 W18A	APP CRS 177°	Rwy Ldg 9503 TDZE 23 Apt Elev 25

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, increase LNAV/VNAV Cat E visibility to 1½ mile and increase LNAV Cats C, D and E visibility to RVR 6000.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 500 then climbing right turn to 3000 direct PLANN and hold, continue climb-in-hold to 3000.

ATIS	MYRTLE BEACH APP CON*	MYRTLE BEACH TOWER*	GND CON	CLNC DEL	UNICOM
123.925	(171° - 321°) 127.4 257.95 (322° - 170°) 119.2 350.3	128.45 (CTAF) L 259.3	120.3 275.8	120.3	122.95





CATEGORY	A	B	C	D	E
LPV DA*	223/24 200 (200-½)				
LNAV/VNAV DA	465/50 442 (500-1)				
LNAV MDA	440/24 417 (500-½)		440/40 417 (500-¾)		
CIRCLING	560-1 535 (600-1)		700-2 675 (700-2)	700-2¼ 675 (700-2¼)	700-2½ 675 (700-2½)

SE-2, 30 OCT 2025 to 27 NOV 2025

SE-2, 30 OCT 2025 to 27 NOV 2025