

WAAS CH 42910 W06A	APP CRS 063°	Rwy Ldg TDZE 156 Apt Elev 164	5001
--	------------------------	---	-------------

RNAV (GPS) RWY 6

HUDSON VALLEY RGNL (POU)

⚠

Circling NA to Rwy's 7 and 25. Baro-VNAV NA when using Montgomery altimeter setting.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 49°C (120°F). Circling Rwy 15, 33 NA at night. Rwy 6 helicopter visibility reduction below ¾ SM NA. Rwy 15, 33 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Montgomery altimeter setting: increase LPV DA to 574; increase LNAV/VNAV DA to 809 and all Cats visibility ¼ SM; increase all MDA 80 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ SM; inop table does not apply to LNAV Cats A/B; for inop ALS, increase LPV all Cats visibility to 1 ½ SM. For inop ALS when using Montgomery altimeter setting, increase LPV all Cats visibility to 1 ½ SM, LNAV/VNAV all Cats visibility to 2 SM and LNAV Cats C/D to 1 ½ SM.

MALSR

MISSED APPROACH:

Climb to 3000 direct JURIL and on track 061° to IGN
VOR/DME and hold, continue climb-in-hold to 3000.

ATIS 126.75	NEW YORK APP CON 132.75 363.1	DUTCHESS COUNTY TOWER ★ 124.0 (CTAF) 0 269.15	GND CON 121.8	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------

4 NM Holding Pattern

CANTY

3200 ← 243° 063° →

GP 3.00° TCH 58

WEXIR 2200

VIYUP 3 NM to RW06

RW06

*1160

* LNAV only.

CATEGORY	A	B	C	D
LPV DA	503-1 347 (400-1)			
LNAV/VNAV DA	738-1 ½ 582 (600-1 ½)			
LNAV MDA	740-1 584 (600-1)		740-1 ¼ 584 (600-1 ¼)	
CIRCLING	760-1 596 (600-1)	840-1 676 (700-1)	940-2 ¼ 776 (800-2 ¼)	1080-3 916 (1000-3)

ELEV 164 D TDZE 156

MIRL Rwy 15-33
HIRL Rwy 6-24
REIL Rwy 24
REIL Rwy 33

POUGHKEEPSIE, NEW YORK

Orig-F 30DEC21

41°38'N-73°53'W

HUDSON VALLEY RGNL (POU)

RNAV (GPS) RWY 6