



WAAS CH 86418 W12A	APP CRS 116°	Rwy Ldg 10000 TDZE 9 Apt Elev 9
--	------------------------	--

RNAV (GPS) Y RWY 12

OAKLAND SAN FRANCISCO BAY (OAK)

▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C (32°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. #RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR	MISSED APPROACH: Climb direct HISIS to cross HISIS at or below 1600, then climb to 5400 on track 111° to DECOT and hold, continue climb-in-hold to 5400.
--	------------------------------	--

D-ATIS 133.775	NORCAL APP CON 125.35 263.15	OAKLAND TOWER 118.3 291.65 (10L/R-28L/R, 15-33) 127.2 256.9 (12-30)	GND CON 121.9 (10L/R-28L/R, 15-33) 121.75 (12-30)
--------------------------	--	---	---



VGSI and RNAV glidepath not coincident (VGSI Angle 2.75/TCH 70).			
ALCAT PLAZA ILATE RW12 HISIS DECOT			
GP 2.75° TCH 55			
2700 1800 1600 5400			
*1080			
*1 NM to RW12			
*LNAV only.			
6.1 NM			
2.5 NM			
1 NM			
CATEGORY	A	B	C
LPV DA#	209/24	200 (200-½)	
LNAV/VNAV DA	304/27	295 (300-⅝)	
LNAV MDA	360/24	351 (400-½)	360/30 351 (400-⅝)
CIRCLING	560-1	551 (600-1)	660-1¾ 651 (700-1¾) 1380-3 1371 (1400-3)