


WAAS CH 82514 W23A	APP CRS 226°	Rwy Ldg 7031 TDZE 3067 Apt Elev 3080
--	------------------------	---

RNAV (GPS) Y RWY 23

ROBERTS FLD (RDM)

T A ❄ -16°C	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 53°C (128°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to 1 SM.	MALSR 	MISSED APPROACH: Climb to 8500 direct WELPU and on track 138° to URBIA and hold, continue climb-in-hold to 8500.
---	--	---	--

ATIS 119.025	SEATTLE CENTER 126.15 269.475	REDMOND TOWER★ 124.5 (CTAF) 0 256.8	GND CON 121.8	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------



ELEV 3080 **D** TDZE 3067

REIL Rwy 5, 11, and 29 **D**
 HIRL Rwy 5-23 **D**
 MIRL Rwy 11-29 **D**

CATEGORY	A	B	C	D
LPV DA	3267- $\frac{1}{2}$ 200 (200- $\frac{1}{2}$)			
LNAV/VNAV DA	3383- $\frac{5}{8}$ 316 (400- $\frac{5}{8}$)			
LNNAV MDA	3440- $\frac{1}{2}$ 373 (400- $\frac{1}{2}$)		3440- $\frac{3}{4}$ 373 (400- $\frac{3}{4}$)	
CIRCLING	3540-1 460 (500-1)	3560-1 480 (500-1)	3640-1 $\frac{1}{2}$ 560 (600-1 $\frac{1}{2}$)	3760-2 $\frac{1}{4}$ 680 (700-2 $\frac{1}{4}$)