

ATIS 132.375
CLNC DEL
119.7
GND CON
121.9 257.8
ROANOKE DEP CON
133.225 339.8
ROANOKE TOWER
118.3 257.8

RNAV 1 - DME/DME/IRU or GPS required.

RADAR required for non-GPS equipped aircraft.

TOP ALTITUDE:
5000

The diagram illustrates the BUFYI FOUR DEPARTURE (RNAV) route. It begins at BUFYI (marked with a triangle in a circle) and proceeds on a track of 267° (11) to PHLP (marked with a diamond). From PHLP, the track changes to 250° (16) to NTHEN (marked with a diamond). From NTHEN, the track changes to 238° to the final point 1675 (marked with a cross). A Minimum Safe Altitude (MSA) circle is shown for ROA at 5600 NM, centered on a compass rose. The route is shown as a series of connected line segments with arrows indicating the direction of flight.

TAKEOFF MINIMUMS:
Rwys 6, 16, 34: NA-Air Traffic.
Rwy 24: Standard with minimum climb
of 500' per NM to 1675.

NOTE: Chart not to scale.

▼

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 24: Climb on heading 238° to 1675, then direct NTHEN, then on track 250° to PHLP, then on track 267° to BUFYI, thence...

...maintain 5000, expect filed altitude within 10 minutes after departure.