

LOC/DME I-SZK

111.1

Chan 48

APP CRS

072°

Rwy Idg

6800

TDZE

1175

Apt Elev

1175

LDA Y RWY 6

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A.)

RADAR required for procedure entry. ADF required.
DME or RADAR required for LOC only.

▼

▲

❄️

For inop ALS, increase S-LDA 6 visibility Cats A/B to 1 3/8 SM.
Circling NA northwest of Rwy 6-24. Inop table does not apply to S-LDA 6 Cats C and D. Inop table does not apply to S-LDA/GS 6 all Cats.

-12° C

MALS

MISSED APPROACH: Climb to 2200 then climbing right turn to 5000 direct VIT NDB and hold, continue climb-in-hold to 5000.

ATIS

132.375

ROANOKE APP CON

133.225 339.8

ROANOKE TOWER

118.3 257.8

GND CON

121.9 257.8

LDA/GLIDE SLOPE

One Minute Holding Pattern

VGSI and LDA glidepath not coincident (VGSI Angle 3.00/TCH 58).

2200

5000

VIT

EXUNE

I-SZK 15.4

SAGEY

I-SZK 12.7

RAMKE

I-SZK 9.9

SKIRT OM

I-SZK 4.9

JOKNI

I-SZK 1.4

5600

5300

252°

072°

4500

4300

2680

2698

GS 3.00°

TCH 55

2.7 NM

2.7 NM

5 NM

3.5

1.2

CATEGORY

A

B

C

D

S-LDA/GS 6

1857-2

682 (700-2)

S-LDA 6

1880-1

705 (800-1)

1880-2

705 (800-2)

CIRCLING

1880-1 1/2

705 (800-1 1/2)

2460-3

1285 (1300-3)

2800-3

1625 (1700-3)

ELEV 1175

TDZE 1175

REIL Rwys 6 and 24

HIRL Rwys 6-24 and 16-34

FAF to MAP 8.5 NM

Knots	60	90	120	150	180
Min:Sec	8:30	5:40	4:15	3:24	2:50

ROANOKE, VIRGINIA

Amtd 13 05SEP24

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A.)

37°20'N-79°59'W

LDA Y RWY 6