

LOC I-JOU 111.1	APP CRS 210°	Rwy Ldg TDZE 1430 Apt Elev 1430
---------------------------	------------------------	---

ILS or LOC RWY 21

JOE FOSS FLD (FSD)

⚠

⚠

❄

For inop ALS, increase S-LOC 21 Cats C/D visibility to 1 1/2 SM and S-LOC 21 WADRI fix minimums Cats C/D visibility to RVR 5500.

-30°C

MALSR

MISSED APPROACH: Climb to 3400 then right turn direct FSD VORTAC and hold.

ATIS 126.6	SIoux FALLS APP CON* 125.8 284.725	SIoux FALLS TOWER* 118.3 (CTAF) 257.8	GND CON 121.9 348.6	UNICOM 122.95
----------------------	--	---	-------------------------------	-------------------------

CATEGORY	A	B	C	D
S-ILS 21	1630/18		200 (200-1/2)	
S-LOC 21	2100/24	670 (700-1/2)	2100-1 1/2	670 (700-1 1/2)
CIRCLING	2100-1	670 (700-1)	2100-1 3/4	2200-2 1/2
WADRI FIX MINIMUMS				
S-LOC 21	1800/24	370 (400-1/2)	1800/35	370 (400-3/4)
CIRCLING	1980-1	550 (600-1)	2060-1 3/4	2200-2 1/2

SIoux FALLS, SOUTH DAKOTA

Amdt 10D 07AUG25

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 21