

WAAS CH 99323 W21A	APP CRS 210°	Rwy Ldg TDZE 1430 Apt Elev 1430
--	------------------------	---

RNAV (GPS) RWY 21

JOE FOSS FLD (FSD)

RNP APCH - GPS.

⚠

⚠

⚠

ASR

-30°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.

MALSR

⬆

⬆

⬆

AS

MISSED APPROACH: Climb to 4000 direct KASME and hold.

ATIS 126.6	SIoux FALLS APP CON★ 125.8 284.725	SIoux FALLS TOWER★ 118.3 (CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95
----------------------	--	---	-------------------------------	-------------------------

4 NM

30°

210°

3100'

(F/F) RAPNE

RULYO 2.6 NM to RW21

1594

RW21

4000

4000

4500

30 NM to MOPUE (NoPT)

120°

120°

300°

300°

4 NM to MOPUE

30 NM to MOPUE

MISSED APCH FIX

KASME

030°

210°

4 NM

4000	KASME	MOPUE	4 NM Holding Pattern	030°	210°	3100	2300	1.2 NM to RW21	1.4 NM	2.5 NM	7 NM
RW21	RULYO 2.6 NM to RW21	RAPNE									
GP 3.00°	TCH 49										
CATEGORY	A	B	C	D							
LPV DA		1630/18	200 (200-½)								
LNAV/VNAV DA		1704/24	274 (300-½)								
LNAV MDA	1860/24	430 (500-½)	1860/40	430 (500-¾)							
CIRCLING	1980-1	550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)							

ELEV 1430

TDZE 1430

210°

4 NM

3100'

4000

4500

30 NM to MOPUE (NoPT)

120°

120°

300°

300°

4 NM to MOPUE

30 NM to MOPUE

MISSED APCH FIX

KASME

030°

210°

4 NM

SIoux FALLS, SOUTH DAKOTA

Amdt 2A 30OCT25

43°35'N-96°45'W

JOE FOSS FLD (FSD)

RNAV (GPS) RWY 21