

WAAS CH 50344 W36B	APP CRS 360°	Rwy Ldg TDZE 678 Apt Elev 678
--	------------------------	---

RNAV (GPS) RWY 36L
TULSA INTL (TUL)

RNP APCH - GPS.




Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations.

MISSED APPROACH:
Climb to 3500 direct AXIWU and hold.

ASR


D-ATIS 124.9 377.2	TULSA APP CON 124.0 338.3	TULSA TOWER 121.2 310.8 (08/26, 18L/36R) 118.7 257.8 (18R/36L)	GND CON 121.9 348.6
------------------------------	-------------------------------------	--	-------------------------------




ELEV 678  TDZE 678

TDZ/CL Rwy 36R
HIRL All Rwys
REIL Rwys 8, 18R and 36L

4 NM Holding Pattern



SUSNE 17500 360° 180°
GP 3.00° TCH 45



PASIE 2400
TREEO 1.7 NM to RW36L
RW36L 1260



3500 AXIWU

CATEGORY	A	B	C	D
LPV DA	928-3/4 250 (300-3/4)			
LNAV/VNAV DA	1088-1 1/8 410 (500-1 1/8)			
LNAV MDA	1120-1 442 (500-1)	1120-1 3/8 442 (500-1 3/8)		
CIRCLING	1120-1 442 (500-1)	1160-1 482 (500-1)	1500-2 1/2 822 (900-2 1/2)	1520-2 3/4 842 (900-2 3/4)

SC-1, 30 OCT 2025 to 27 NOV 2025

SC-1, 30 OCT 2025 to 27 NOV 2025