

WAAS
CH 81813
W31A

APP CRS
309°

Rwy Idg
TDZE
Apt Elev

5997
174
178

RNAV (GPS) RWY 31

Alice Intl (ALI)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using Nueces County altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Nueces County altimeter setting: increase LPV DA to 494 feet, LNAV/VNAV DA to 524 feet; increase all MDA 60 feet and LNAV Cat C and D, and Circling Cat D visibility ¼ SM. For inop ALS, increase all LPV and LNAV/VNAV visibilities to ¾ SM. For inop ALS with Nueces County altimeter setting, increase all LPV visibilities to ¾ SM and LNAV Cat C and D visibility to 1⅛ SM.

MALS

2100

2100

MISSED APPROACH:

Climb to 2100 direct UWAGO and hold.

ASOS 119.225	KINGSVILLE APP CON ★ 119.9 290.45	UNICOM 123.0 (CTAF) 0
-----------------	--------------------------------------	--------------------------

MISSED APCH FIX

129°

308°

4 NM

UWAGO

692

556

267 ±

197 ±

378 ±

570

813

692

556

267 ±

197 ±

378 ±

570

813

Procedure NA for arrivals at CRP VORTAC on airway radials 169 CW 305.

CORPUS CHRISTI
CRP

2600
228°
(24.1)

255°

(FAF)
CITCU

1800
309°
(5)

(IAF)
EDERY

2600 NoPT
216°
(5)

129°

(IF/IAF)
ITDAZ

309°

4 NM

HOLD
14000
2600

2600 NoPT
315° (23.2)

(IAF)
LOCOE

MSA RW31 25 NM

2200

ELEV 178

TDZE 174

2100

UWAGO

ITDAZ

4 NM Holding Pattern

129°

309°

14000

2600

GP 3.00°

TCH 47

1 NM to RW31

3.9 NM

6 NM

1800

CITCU

309°

129°

230

5997 X 100

4490 X 100

35

309°

REIL Rwy 13 0

MIRL Rwy 13-31 and 17-35 0

CATEGORY	A	B	C	D
LPV DA		437-¾	263 (300-¾)	
LNAV/VNAV DA		467-¾	293 (300-¾)	
LNAV MDA		520-¾	346 (400-¾)	
CIRCLING	600-1 422 (500-1)	640-1 462 (500-1)	700-1½ 522 (600-1½)	900-2¼ 722 (800-2¼)

Alice, Texas

27°44'N-98°02'W

Alice Intl (ALI)

Amclt 1G 05OCT23

RNAV (GPS) RWY 31