

APP CRS

Rwy Ldg

006°

TDZE

6300

6431

Apt Elev

6451

RNAV (RNP) Z RWY 1

JACKSON HOLE (JAC)

RNP AR APCH

▽

-21°C

For uncompensated Baro-VNAV systems, procedure NA below -27°C or above 54°C.
Inop table does not apply to RNP 0.11* all Cats visibility.
For inop ALS, increase RNP 0.30* all Cats visibility to ¾ SM.
Missed approach requires RNP less than 1.0.

MALS

MISSED APPROACH: Climb to 14000 on track 007° to UBEVE and track 007° to QUIRT and track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.
* Missed approach requires minimum climb of 330 feet per NM to 8200; if unable to meet climb gradient, see RNAV (RNP) Y RWY 1.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER*	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF)	124.55	122.95

VUGUY	UYET	NECPI	YONUL	JEVIM	WIDGA	RW01
15000	11600	11200	10500	9900	8600	
GP 3.00°						
TCH 50						
	12 NM	2 NM	2.4	2.4	7.9 NM	6.7 NM
CATEGORY	A	B	C	D		
RNP 0.11 DA*		6690-¾	259 (300-¾)			
RNP 0.30 DA*		6743-¾	312 (300-¾)			

AUTHORIZATION REQUIRED

JACKSON, WYOMING

Amtd 1 13SEP18

43°36'N-110°44'W

JACKSON HOLE (JAC)

RNAV (RNP) Z RWY 1