

LOC/DME I-EVV
109.9
Chan **36**

APP CRS
221°

Rwy Ldg
TDZE **422**
Apt Elev **422**

ILS or LOC RWY 22

EVANSVILLE RGNL (E V V)

RADAR or DME required for procedure entry at AUGUS.

⚠

Circling Rwy 9 NA at night. For inop ALS, increase S-LOC 22 Cats C and D visibility to 1¾ SM. DME minimums: For inop ALS, increase S-LOC 22 Cats C and D visibility to RVR 6000. * RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 2500 direct PXV VORTAC and hold.

ATIS 120.2	EVANSVILLE APP CON ★ 124.025 290.9	EVANSVILLE TOWER ★ 118.7(CTAF) 257.8	GND CON 121.9	CLNC DEL 126.6	UNICOM 122.95
----------------------	--	--	-------------------------	--------------------------	-------------------------

OWENSBORO
OWB
108.65
Chan 23 (Y)

ALT MISSED
APCH FIX

MSA PXV 25 NM
2500

Procedure NA for arrival on PXV
VORTAC airway radials 355 CW 151.

POCKET CITY
113.3 PXV
Chan 80

2500 NoPT
221° (7.4)

LOCALIZER 109.9
I-EVV
Chan 36

POCKET CITY
113.3 PXV
Chan 80

1000 2500 PXV

CUYAR INT I-EVV 7.9

1060 2500

1.2 NM 0.9 NM 4.4 NM

CATEGORY	A	B	C	D
S-ILS 22*	622/24 200 (200-½)			
S-LOC 22	1060/24	638 (700-½)	1060-1¾	638 (700-1¾)
CIRCLING	1060-1	638 (700-1)	1060-1¾ 638 (700-1¾)	1060-2 638 (700-2)
ZAGAK FIX MINIMUMS (DME REQUIRED)				
S-LOC 22	840/24	418 (500-½)	840/40	418 (500-¾)
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1¾ 618 (700-1¾)	1040-2 618 (700-2)

ELEV 422 TDZE 422

81 8021 X 150

36 HIRL Rwy 4-22 and 18-36
REIL Rwy 4, 18, and 36
MIRL Rwy 9-27

FAF to MAP 6.4 NM

Knots	60	90	120	150	180
Min:Sec	6:24	4:16	3:12	2:34	2:08

EVANSVILLE, INDIANA
Amdt 24 08SEP22

38°02'N-87°32'W

EVANSVILLE RGNL (E V V)
ILS or LOC RWY 22