


LOC I-SPI	APP CRS	Rwy Ldg	7927
109.5	043°	TDZE	592
		Apt Elev	598

ILS or LOC RWY 4
ABRAHAM LINCOLN CAPITAL (SPI)

ADF Required.		MALSR		MISSED APPROACH: Climb to 1500 then climbing left turn to 2300 direct HUSKK LOM and hold.
When local altimeter setting not received, use Lincoln altimeter setting and increase all DA 57 feet, all MDA 60 feet, increase S-LOC and Circling Cat C/D visibility ¼ mile. For inop ALS when using Lincoln altimeter setting, increase S-LOC 4 Cats C and D visibility to 1¾ SM. ASR *RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Lincoln altimeter setting).				
ATIS	SAINT LOUIS APP CON ★	SPRINGFIELD TOWER ★	GND CON	UNICOM
127.65 270.1	126.15 323.0	121.3 (CTAF) 257.8	121.9 348.6	122.95



One Minute Holding Pattern		SP LOM SPI 5.5	1500	2300	SP
2300 ← 223°		2297	2300	043°	
GS 3.00° TCH 56					
CATEGORY	A	B	C	D	
S-ILS 4		* 792/24 200 (200-½)			
S-LOC 4	1020/24	428 (500-½)	1020/40	428 (500-¾)	
CIRCLING	1040-1 442 (500-1)	1100-1 502 (600-1)	1360-2¼ 762 (800-2¼)	1380-2½ 782 (800-2½)	

