

WAAS CH 99403 W32A	APP CRS 316°	Rwy Idg TDZE 574 Apt Elev 583
--	------------------------	---

RNAV (GPS) RWY 32



FREEMAN MUNI (SEIR)


RNP APCH - GPS.

Baro-VNAV and VDP NA when using Louisville Muhammad Ali Intl altimeter setting. Rwy 32 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Louisville Muhammad Ali Intl altimeter setting and increase LPV DA to 979 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1230 feet and all visibilities ¾ SM; increase all MDAs 120 feet and LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH:
Climb to 2600 direct
RUYOT and hold.

AWOS-3 119.425	LOUISVILLE APP CON 132.075 327.0	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



2600	RUYOT	4 NM Holding Pattern			
					
					
CATEGORY	A	B	C	D	
LPV DA	859-1 285 (300-1)				
LNAV/VNAV DA	1110-1½ 536 (600-1½)				
LNAV MDA	1140-1 566 (600-1)		1140-1½ 566 (600-1½)		
 CIRCLING	1140-1 557 (600-1)		1300-2 717 (800-2)	1300-2¼ 717 (800-2¼)	

EC-2, 30 OCT 2025 to 27 NOV 2025

EC-2, 30 OCT 2025 to 27 NOV 2025