

WAAS CH 97501 W03A	APP CRS 026°	Rwy Ldg 9002 TDZE 4744 Apt Elev 4744
--	------------------------	---

RNAV (GPS) Y RWY 3

IDAHO FALLS RGNL (IDA)

RNP APCH-GPS.


▼

▲

Circling to Rwy 35 NA at night.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27°C or above 54°C.

MISSED APPROACH: Climb to 5200 then climbing left turn to 7500 direct TERRE and hold.

ATIS 135.325	SALT LAKE CENTER 128.35 239.25	IDAHO FALLS TOWER★ 118.5 (CTAF) 0 257.8	GND CON 121.7	CLNC DEL 121.7	GCO 121.725	UNICOM 122.95
------------------------	--	---	-------------------------	--------------------------	-----------------------	-------------------------



7 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	4944-¾ 200 (200-¾)			
LNAV/VNAV DA	5002-¾ 258 (300-¾)			
LNAV MDA	5100-1 356 (400-1)			
CIRCLING	5200-1 456 (500-1)	5300-1 556 (600-1)	5400-1¾ 656 (700-1¾)	5420-2¼ 676 (700-2¼)

ELEV 4744 D TDZE 4744

REIL Rwy 3 0
HIRL Rwy 3-21 0
MIRL Rwy 17-35