

WAAS CH 81912 W06A	APP CRS 061°	Rwy Idg 5765 TDZE 38 Apt Elev 47
--	------------------------	---

RNAV (GPS) RWY 6
NANTUCKET MEML (ACK)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Hyannis altimeter setting. When local altimeter setting not received, use Hyannis altimeter setting and increase LPV DA to 301, LNAV/VNAV DA to 363 and all MDA 80 ft; increase LNAV Cts C/D visibility to RVR 5000 and Circling Cts C/D visibility ¼ SM. Inoperative table does not apply to LPV. For inoperative ALS increase LNAV/VNAV all Cts visibility to RVR 4500, and LNAV C/D visibility to RVR 5500. For inoperative ALS when using Hyannis altimeter setting, increase LPV all Cts visibility to RVR 4500, increase LNAV/VNAV all Cts visibility to RVR 6000 and increase LNAV Cts C/D to 1/8 SM.

MALSF



MISSED APPROACH:
Climb to 1800 direct
WAIVS and hold.

ATIS 127.5	BOSTON APP CON 126.1 318.1	NANTUCKET TOWER ★ 118.3 (CTAF) 0	GND CON 132.5	CLNC DEL 119.375	UNICOM 122.95
----------------------	--------------------------------------	--	-------------------------	----------------------------	-------------------------

