


WAAS CH 42800 W01A	APP CRS 014°	Rwy Ldg TDZE Apt Elev 8784 2170 2181
--	------------------------	--


RNAV (GPS) RWY 1R
HARRY REID INTL (LAS)

RNP APCH - GPS. RADAR required.	MISSED APPROACH: Climb to 2700 then climbing right turn to 7000 direct HAI DN and hold, continue climb-in-hold to 7000.
Rwy 1R helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C or above 54°C.	

D-ATIS 132.4	LAS VEGAS APP CON 125.025 379.15 (West) 119.775 282.2 (East)	LAS VEGAS TOWER 118.75 257.8 (Rwy 1L/19R, 1R/19L) 119.9 257.8 (Rwy 8L/26R, 8R/26L)	GND CON 121.1 270.8 E of 1R/19L 121.9 254.3 W of 1L/19R	CLNC DEL 118.0	CPDLC
------------------------	--	--	---	--------------------------	-------



FEBET		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 76).				2700	7000	HAI DN
GP 3.00° TCH 60		6000	5100	3940	3520			
		014°						
		3.8 NM	3.6 NM	1.3 NM	1.8 NM	2.2 NM		
CATEGORY		A		B		C		D
LPV DA		2458-7⁄8		288 (300-7⁄8)				
LNAV/ VNAV DA		2641-13⁄8		471 (500-13⁄8)				
LNAV MDA		2960-1 790 (800-1)	2960-1¼ 790 (800-1¼)	2960-2½		790 (800-2½)		
CIRCLING		3020-1¼ 839 (900-1¼)	3060-1¼ 879 (900-1¼)	3100-2¾ 919 (1000-2¾)		3540-3 1359 (1400-3)		



SW-4, 30 OCT 2025 to 27 NOV 2025

SW-4, 30 OCT 2025 to 27 NOV 2025