




WAAS CH 72908 W19B	APP CRS 191°	Rwy Ldg 10801 TDZE 991 Apt Elev 1027
--	------------------------	---

RNAV (GPS) Y RWY 19R

KANSAS CITY INTL (MCI)

RNP APCH - GPS. ⚠ LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to RVR 5500. Simultaneous approach authorized except from SCRP and HOLMS.				ALSF-2 	MISSED APPROACH: Climb to 2000 then climbing right turn to 4000 direct RUGBB and hold.
D-ATIS 128.375	KANSAS CITY APP CON 120.95 318.1	INTERNATIONAL TOWER 128.2 254.25	GND CON 121.8	CLNC DEL 135.7	CPDLC



		RUGBB 	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 80).		CAMDO		
ZESAB 1.8 NM to RW19R		PEAKA 2400	BRTNY	WESGI	191° 5000	6000	
RW19R 0.9 NM to RW19R		3300		GP 3.00° TCH 55			
0.9 NM		0.9 NM	2.5 NM	2.8 NM	5.3 NM	3.1 NM	
CATEGORY	A		B		C	D	
LPV DA			1191/18		200 (200-½)		
LNAV/VNAV DA			1417/40		426 (400-¾)		
LNAV MDA	1360/24		369 (400-½)		1360/35 369 (400-⅝)		
CIRCLING	1540-1		513 (600-1)		1540-1½ 513 (600-1½)		1580-2 553 (600-2)