

LOM AW	APP CRS	Rwy Idg	5332
382	342°	TDZE	135
		Apt Elev	142

NDB RWY 34
ARLINGTON MUNI (AWO)



NA

When local altimeter setting not received, use Whidbey Island NAS (Ault Field) altimeter setting: increase all MDA 80 feet and visibility S-34 Cats B, C, and D and Circling Cats B and C ¼ SM. For inop MALS when using Whidbey Island NAS (Ault Field) altimeter setting, increase S-34 Cats C and D visibility to 2½.

MALS

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct AW LOM and hold.

AWOS-3PT 135.625	SEATTLE APP CON 128.5 306.9	CLNC DEL 121.725	CTAF 122.725 0
---------------------	--------------------------------	---------------------	-------------------



		4.7 NM				342°	
CATEGORY	A	B	C	D			
S-34	860-¾ 725 (800-¾)		860-1¾ 725 (800-1¾)				
CIRCLING	860-1	900-1	1000-2½	1040-3			
	718 (800-1)	758 (800-1)	858 (900-2½)	898 (900-3)			
FAF to MAP 4.7 NM							
Knots	60	90	120	150	180		
Min:Sec	4:42	3:08	2:21	1:53	1:34		

NW-1, 30 OCT 2025 to 27 NOV 2025

NW-1, 30 OCT 2025 to 27 NOV 2025