

WAAS CH 72925 W04A	APP CRS 035°	Rwy Idg 5658 TDZE 2380 Apt Elev 2380
--	------------------------	---

RNAV (GPS) RWY 4

AVENGER FLD (SWW)

⚠ Baro-VNAV NA when using Snyder altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 29°C (84°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Snyder altimeter setting and increase LPV DA to 2702 feet and LNAV/VNAV DA to 2799 feet, and all MDAs 80 feet; increase LPV visibility all Cats ½ SM, LNAV/VNAV visibility all Cats ¼ SM, LNAV visibility Cats C/D ¼ SM, and Circling Cats C/D visibility ¼ SM. When VGSi input, Straight-in/ Circling Rwy 4 procedure NA at night. When VGSi input, Circling Rwy 17 and 22 NA at night.

MISSED APPROACH:
Climb to 4400 direct
AWBIR and hold.

AWOS-3 119.025	ABILENE APP CON 127.2 282.3	UNICOM 122.8 (CTAF)
--------------------------	---------------------------------------	-------------------------------

