APP CRS	Rwy Ldg	8003
100°	TDZE	201
	Apt Elev	201

RNAV (GPS) RWY 10
LAKE CITY GATEWAY (LCQ)

RNP APCH - GPS.

Rwy 10 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use GNV altimeter setting and increase all MDAs 100 feet, increase LNAV Cat C/D visibility ⅜ SM and Circling Cat C visibility ½ SM and Cat D ¼ SM. Straight-in Rwy 10 NA at night, Circling Rwy 5, 10, 23 NA at night.

MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct KRKLD and hold.

AWOS-3	JACKSONVILLE CENTER		LAKE CITY TOWER ★	GND CON	UNICOM
120.675	125.375	254.325	119.2 (CTAF) L 314.6	121.9	122.95



ELEV 201	TDZE 201



CATEGORY	A	B	C	D
LNAV MDA	700-1 499 (500-1)		700-1⅜ 499 (500-1⅜)	
CIRCLING	760-1 559 (600-1)		780-1½ 579 (600-1½)	960-2½ 759 (800-2½)

REIL Rwys 10 and 28 L
MIRL Rwys 5-23 and 10-28 L

SE-3, 30 OCT 2025 to 27 NOV 2025

SE-3, 30 OCT 2025 to 27 NOV 2025