

WAAS
CH **45616**
W23A

APP CRS
233°

Rwy Ldg
TDZE
Apt Elev
6215
931
947

RNAV (GPS) Y RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALSF, increase LNAV/VNAV all Cats visibility to 2¼. **RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

(A1)

MISSED APPROACH: Climb to 1400 then dimbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6
----------------------	--	--	-------------------------------

Procedure NA for arrivals at WARDO on V59 northbound.

Procedure NA for arrivals at ITALY on V59 northbound.

Procedure NA for arrival on HVQ VOR/DME airway radials 360 CW 141.

ELEV **947**

D

TDZE **931**

233°

6715 X 150

0.8% UP

(A1)

TWR

1400

3000

HVQ

*LNAV only.

ZUPUT
2.3 NM to RW23

COSIK
2400

ENIVY
6 NM Holding Pattern

1.7 NM to RW23

*1680

2400

GP 3.00°

TCH 56

CATEGORY	A	B	C	D
LPV	DA**	1131/24	200 (200-½)	
LNAV/VNAV	DA	1601-1⅞	670 (700-1⅞)	
LNAV	MDA	1500/24 569 (600-½)	1500-1⅓ 569 (600-1⅓)	
CIRCLING	1600-1	653 (700-1)	1760-2½ 813 (900-2½)	1760-2¾ 813 (900-2¾)

CHARLESTON, WEST VIRGINIA

Amdt 1B 07DEC17

38°23'N-81°36'W

WEST VIRGINIA INTL YEAGER (CRW)

RNAV (GPS) Y RWY 23