

WAAS CH 77913 W32A	APP CRS 321°	Rwy Ldg TDZE 222 Apt Elev 258
--	------------------------	---

RNAV (GPS) RWY 32

SHREVEPORT RGNL (SHV)

RNP APCH.

▼

▲


ASR

Rwy 32 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cat A and B visibility to RVR 5500.


MALSR


MISSED APPROACH:
Climb to 2600 direct
BABYE and hold.

ATIS 128.45	SHREVEPORT APP CON 119.9 335.55	SHREVEPORT TOWER 121.4 236.775	GND CON 121.175 236.775	CLNC DEL 124.65
-----------------------	---	--	-----------------------------------	---------------------------



ELEV 258	D	TDZE 222
----------	----------	----------



2600	BABYE				
					
*LNAV only.					
					
CATEGORY	A	B	C	D	
LPV DA	422/40		200 (200-¾)		
LNAV/VNAV DA	629/40		407 (400-¾)		
LNAV MDA	680/40	458 (500-¾)	680/45	458 (500-¾)	
CIRCLING	760-1	502 (600-1)	980-2 722 (800-2)	1100-2¾ 842 (900-2¾)	