

APP CRS

354°

Rwy Idg

3251

TDZE

860

Apt Elev

861

RNAV (GPS) RWY 35

HOLDENVILLE MUNI (F99)

RNP APCH-GPS.

▼

Rwy 35 helicopter visibility reduction below 1 SM NA.

▲ NA

Straight-In and Circling Rwy 35 NA at night.

Use Ada altimeter setting.

MISSED APPROACH: Climb to 3000 direct ADIXE and hold.

|                         |                                   |               |
|-------------------------|-----------------------------------|---------------|
| ADH AWOS-3PT<br>118.725 | FORT WORTH CENTER<br>132.2 338.35 | CTAF<br>122.9 |
|-------------------------|-----------------------------------|---------------|

The main chart illustrates the RNAV (GPS) approach for RWY 35. The path starts from WAGAS (30 NM) and JIPIT (30 NM), both with a 174° heading and 3000 ft altitude. The path proceeds through HEPER (30 NM, 084°/264°), MIMUW (5 NM, 354°), and ADIXE (4 NM, 174°/354°) before reaching RWY 35. Key altitudes include 1589, 1300, 1320, 1028, 1067, 1297, 2500, and 3000 ft. A holding pattern is shown at HEPER with a 4 NM radius and 3000 ft altitude. The chart also shows a missed approach procedure: climb to 3000 ft and hold at ADIXE.

ELEV 861

TDZE 860

4 NM Holding Pattern

HEPER

MIMUW

RW35

ADIXE

| CATEGORY | A                     | B                     | C                       | D  |
|----------|-----------------------|-----------------------|-------------------------|----|
| LNAV MDA | 1420-1                | 560 (600-1)           | 1420-1½<br>560 (600-1½) | NA |
| CIRCLING | 1460-1<br>599 (600-1) | 1660-1<br>799 (800-1) | 1760-2¾<br>899 (900-2¾) | NA |

MIRL Rwy 17-35

35

354°

HOLDENVILLE, OKLAHOMA

Orig-B 06OCT22

35°05'N-96°25'W

RNAV (GPS) RWY 35

HOLDENVILLE MUNI (F99)