

MUNCIE, INDIANA

AL-5011 (FAA)

25219

WAAS CH 78237 W03A	APP CRS 025°	Rwy Ldg 5197 TDZE 937 Apt Elev 937
--	------------------------	---

RNAV (GPS) RWY 3

DELAWARE COUNTY RGNL (MIE)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all DA 121 feet and all MDA 140 feet; increase LPV all Cats and LNAV Cats C/D visibility ¾ mile, LNAV/VNAV all Cats visibility ¾ mile and Circling Cats C/D visibility ½ mile. Baro-VNAV NA when using Fort Wayne Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2800 direct
IFECA and hold.

ATIS 133.25	INDIANAPOLIS APP CON 120.65 317.8	MUNCIE TOWER ★ 120.1 (CTAF) 0	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------

RADAR REQUIRED

MISSED APCH FIX

4 NM



507

IFFCA

MSA RW03 25 NM

2900

ELEV	937	D	TDZE	937
------	-----	----------	------	-----

HIRL Rwy 14-32 **L**MIRL Rwy 3-21 **L**REIL Rwy 3, 14 and 21 **L**

4 NM Holding Pattern

APPAL

CESUD

HABIP

2800

2600

2600

2800

IFECA

GP 3.00°
TCH 39

205°

025°

025°

1640

7.5 NM

3 NM

0.9 NM

1.2 NM

RW03

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	1190-7 ₈ 253 (300-7 ₈)			
LNAV/VNAV DA	1412-1 ⁵ ₈ 475 (500-1 ⁵ ₈)			
LNAV MDA	1360-1 423 (500-1)		1360-1 ¹ ₄ 423 (500-1 ¹ ₄)	
CIRCLING	1460-1 523 (600-1)		1500-1 ¹ ₂ 563 (600-1 ¹ ₂)	1600-2 663 (700-2)

MUNCIE, INDIANA
Orig 05MAR15

40°15'N-85°24'W

DELAWARE COUNTY RGNL (MIE)
RNAV (GPS) RWY 3

EC-2, 30 OCT 2025 to 27 NOV 2025