


VOR/DME MIE	APP CRS	Rwy Ldg
114.4	201°	5197
Chan 91		TDZE 935
		Apt Elev 937

VOR RWY 21
DELAWARE COUNTY RGNL (MIE)


▼ Visibility reduction by helicopters NA. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all MDAs 140 feet; increase S-21 Cat C visibility ½ SM and Cat D visibility ¼ SM; increase Circling Cat C visibility ½ SM and Cat D ¼ SM; DUNKI fix minimums: increase S-21 Cat C/D ¾ SM and Circling visibility Cat C/D ½ SM. VDP NA when using Fort Wayne Intl altimeter setting.

MISSED APPROACH:
Climb to 2200 then climbing left turn to 2600 direct MIE VOR/DME and hold.

ATIS 133.25	INDIANAPOLIS APP CON 120.65 317.8	MUNCIE TOWER★ 120.1 (CTAF) 0	GND CON 121.9	UNICOM 122.95
----------------	--------------------------------------	---------------------------------	------------------	------------------



ELEV 937	D	TDZE 935
----------	---	----------



2200	2600	MIE	MIE VOR/DME 2600 Remain within 10 NM 021° 2500 201° 1500* MIE 2.2 DUNKI INT MIE 3 0.7 1.5 NM 0.8 NM			
*1640 when using Fort Wayne Intl altimeter setting.						
CATEGORY	A	B	C	D		
S-21	1500-1 565 (600-1)		1500-1½ 565 (600-1½)	1500-1¾ 565 (600-1¾)		
CIRCLING	1500-1 563 (600-1)		1500-1½ 563 (600-1½)	1560-2 623 (700-2)		
DUNKI FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)						
S-21	1440-1 505 (600-1)		1440-1½ 505 (600-1½)			
CIRCLING	1460-1 523 (600-1)		1480-1½ 543 (600-1½)	1560-2 623 (700-2)		