

WAAS CH 61013 W30A	APP CRS 304°	Rwy Idg 4999 TDZE 9 Apt Elev 9
--	------------------------	---

RNAV (GPS) RWY 30

HOUMA-TERREBONNE (HUM)



▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase LPV DA to 336, LNAV/VNAV DA to 489, and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ⅜ SM. Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 1800 direct NACIV and hold.

ATIS 120.25	NEW ORLEANS APP CON 118.9 350.35	HOUMA TOWER★ 125.3 (CTAF) 0 346.3	GND CON 123.875	CLNC DEL 118.9 (When twr closed)	UNICOM 122.95
-----------------------	--	---	---------------------------	---	-------------------------



1800

↑

NACIV

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 39).

4 NM
Holding Pattern

* LNAV only

KEBCE

1.6 NM to RW30

RECYO

HOVPU

1800

124°

304°

304°

560*

1800

GP 3.00°

TCH 45

1.6 NM

3.8 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	259-¾ 250 (300-¾)			
LNAV/VNAV DA	412-1⅞ 403 (500-1⅞)			
LNAV MDA	380-1 371 (400-1)			
CIRCLING	480-1 471 (500-1)	760-2¼ 751 (800-2¼)	760-2½ 751 (800-2½)	