

▼

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned by ATC, thence....

TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned by ATC, thence....

....for RADAR vectors to JWELS, then on track 218° to SNDRS, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

BGHR T TRANSITION (SNDRS3.BGHR T):

TORRR TRANSITION (SNDRS3.TORRR):

TOP ALTITUDE:
ASSIGNED BY ATC

RNAV-1 DME/DME/IRU or GPS.
RADAR required.

DETROIT DEP CON
132.35 284.0
ATIS
125.025
CLNC DEL
118.25
GND CON
121.9
PONTIAC TOWER★
120.5 (CTAF)

N

←275°→

←095°→

NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.

NOTE: TORRR Transition: For use by KIND and KCVG area arrivals only and flights filed at or below FL220, or as assigned by ATC.

BGHR T

8000
*2400

269°
(94)

KNRKO

8000
*2200

264°
(28)

SEABS

8000
*2400

265°
(30)

REEDA

8000
*2400

255°
(24)

SNDRS

8000
*2400

271°
(31)

JWELS

209°
(33)

TORRR

TAKEOFF MINIMUMS:
Rwys 18, 36: NA - Environmental.
Rwys 9L/R, 27L/R: Standard.

NASA PTK 25 NM

2900

NOTE: Chart not to scale.

(SNDRS3.SNDRS) 16MAY24

SNDRS THREE DEPARTURE (RNAV)

OAKLAND COUNTY INTL (PTK)
PONTIAC, MICHIGAN

EC-1, 30 OCT 2025 to 27 NOV 2025