

WAAS
CH **93702**
W06A

APP CRS
057°

Rwy Ldg
TDZE
Apt Elev

7201
2351
2351

RNAV (GPS) RWY 6

GENERAL WM J FOX AIRFIELD (WJF)

▼

When VGSI inop, Straight-in/Circling Rwy 6 procedure NA at night.

▲

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 45°C (113°F). When local altimeter setting not received, use Palmdale altimeter setting: increase LPV DA to 2661 feet, LNAV/VNAV DA to 2709 feet and all MDAs 60 feet, and increase Circling Cats C/D visibility ¼ SM. Baro-VNAV NA when using Palmdale altimeter setting.

MISSED APPROACH: Climb to 6000 direct SISOY and via 091° track to ETHER and hold.

ATIS 126.3	JOSHUA APP CON 126.1 290.3	FOX TOWER* 118.525 (CTAF) 256.9	GND CON 121.7 256.9	UNICOM 122.95
----------------------	--------------------------------------	---	-------------------------------	-------------------------

MISSED APCH FIX

ETHER

249°

069°

7 NM

ELEV 2351

TDZE 2351

JILMU		HONUL		GUVDE		6000	SISOY	tr 091°	ETHER						
7000		057°		6400		5500		*4100							
Procedure Turn NA		GP 3.00°		TCH 40		HURIM 5.4 NM to RW06		*LNAV only.							
2.7 NM		3.5 NM		4.1 NM		5.4 NM		RW06							
CATEGORY	A	B		C		D									
LPV DA	2601-1		250 (300-1)												
LNAV/VNAV DA	2649-1		298 (300-1)												
LNAV MDA	2940-1	589 (600-1)		2940-1½	589 (600-1½)	2940-1¾									
CIRCLING	2940-1		589 (600-1)	3120-2½		3120-2½									
				769 (800-2¼)		769 (800-2¼)									
REIL Rwy 6 and 24 MIRL Rwy 6-24															

LANCASTER, CALIFORNIA

Orig-A 09SEP21

34°44'N-118°13'W

GENERAL WM J FOX AIRFIELD (WJF)

RNAV (GPS) RWY 6