


WAAS CH 86310 W12A	APP CRS 121°	Rwy ldg 10501 TDZE 310 Apt Elev 312
--	------------------------	--

RNAV (GPS) RWY 12
WASHINGTON DULLES INTL (IAD)

RNP APCH - GPS. ▼ For inop ALS, increase LNAV Cats C/D visibility to RVR 6000. ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C.		MALSR 	MISSED APPROACH: Climb to 5000 direct OTSUE and on track 199° to ZULKA and right turn on track 298° to OLVR and hold.
D-ATIS 134.85	POTOMAC APP CON 120.45 306.925 (241°-330°) 128.525 306.925 (091°-240°) 126.1 338.25 (331°-090°)	DULLES TOWER 120.1 317.8 (Rwy 1R/19L) 120.25 348.6 (Rwy 1C/19C) 134.425 348.6 (Rwys 1L/19R and 12/30)	GND CON 121.9 317.8 (EAST) 121.625 348.6 (WEST)



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66).		5000	OTSUE	ZULKA	OLVR
KNUCK		↑	tr 199°	tr 298°	△
JETMO		1700	OKRAE 2.6 NM to RW12	1.1 NM to RW12	
Procedure Turn NA		4500	1700	1180	
GP 3.00°		10.9 NM	1.6 NM	1.5 NM	1.1 NM
TCH 49					
CATEGORY	A	B	C	D	
LPV DA		510/18	200 (200-½)		
LNAV/VNAV		737/50	427 (500-1)		
LNAV MDA	720/24	410 (500-½)	720/40	410 (500-¾)	
CIRCLING	940-1	628 (700-1)	940-1¾ 628 (700-1¾)	1180-2¾ 868 (900-2¾)	
ELEV 312		D		TDZE 310	
WASHINGTON, DC		38°57'N-77°28'W		WASHINGTON DULLES INTL (IAD)	
Amdt 1F 26DEC24				RNAV (GPS) RWY 12	

