



WAAS CH 45921 W20A	APP CRS 195°	Rwy Idg 7571 TDZE 757 Apt Elev 759
--	------------------------	---

RNAV (GPS) RWY 20R

DUPAGE (DPA)

RNP APCH - GPS.		MISSED APPROACH: Climb to 2500 direct FABUG and 187° track to JOT VOR/DME and hold.		
⚠ Circling Rwy 15, 28, 33 NA at night. ⚠ Rwy 20R helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.				
ATIS 132.075	CHICAGO APP CON 133.5 349.0	DUPAGE TOWER 120.9 257.8	GND CON 121.8	CLNC DEL 119.75



2500	FABUG	tr 187°	JOT				
				SUCOP 1.8 NM to RW20R	FRTZZ 2500	4 NM Holding Pattern	
				1.1 NM to RW20R	2500	015° → 6000 ← 195° 3000	GP 3.00° TCH 40
				1.1 NM	0.6	3.6 NM	6.2 NM
CATEGORY		A		B	C	D	
LPV DA		1043-7/8		286 (300-7/8)			
LNAV/VNAV DA		1080-1		323 (400-1)			
LNAV MDA		1160-1 403 (500-1)		1160-1 1/8 403 (500-1 1/8)			
CIRCLING		1260-1 501 (600-1)		1360-1 601 (700-1)		1460-2 701 (800-2)	
						1460-2 1/4 701 (800-2 1/4)	