

APP CRS
272°

Rwy Ldg
7000

TDZE
701

Apt Elev
703

COPTER RNAV (GPS) RWY 27

HAGERSTOWN RGNL/RICHARD A HENSON FLD (HGR)

▼

Inop table does not apply.
DME/DME RNP-0.3 NA. VDP NA with Martinsburg altimeter setting.
When local altimeter setting not received, use Martinsburg altimeter setting and increase MDA 80 feet.

MALSR

MISSED APPROACH: Climb to 1200 then climbing right turn to 2500 direct YIYUN and hold.

ASOS 126.375	POTOMAC APP CON 126.825 239.025	HAGERSTOWN TOWER ★ 120.3 (CTAF) 0 225.4	GND CON 120.8	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------

4 NM

YIYUN

Limit initial and intermediate approach to 90K.
Limit final and missed approach to 70K.
Increase to 90K upon reaching the missed approach altitude.

(IAF) WOXZU

2500

182°

(3)

(IF) NOLIN

1800

272°

(4.8)

(FAF) JOMES

795±

Δ

RW27

(IAF) VECDU

2500

017°

(3)

P-40 R-4009

ELEV 703

D

TDZE 701

MSA RW27 25 NM

3700

TWR

7000 X 150

272°

0.3% UP

0.3%

2

1200

2500

YIYUN

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 55).

4.98°

HCH 55

1 NM to RW27

1800

272°

2500

NOLIN

JOMES

1 NM

1 NM

4.8 NM

RW27

REIL Rwy 2 and 20

REIL Rwy 9 0

MIRL Rwy 2-20

HIRL Rwy 9-27 0

CATEGORY	COPTER
LNAV MDA	1060-1/2 359 (400-1/2)

HAGERSTOWN, MARYLAND

Orig-A 22JUN17

HAGERSTOWN RGNL/RICHARD A HENSON FLD (HGR)

39°43'N-77°44'W

COPTER RNAV (GPS) RWY 27