

LOC I-BRD
109.9

APP CRS
231°

Rwy Ldg
TDZE **1224**
Apt Elev **1232**

ILS or LOC RWY 23
BRainerd Lakes RGNL (BRD)

ADF required. When local altimeter setting not received, use Aitkin altimeter setting and increase all DAs 52 feet and all MDAs 60 feet. Increase S-LOC Cat C visibility to 1 SM and Circling Cat D visibility to 2¼ SM.

MALSRR

AS

MISSED APPROACH: Climb to 2100 then climbing right turn to 3000 direct LAREW LOM and hold.

ASOS
126.775

MINNEAPOLIS CENTER
118.05 239.0

UNICOM
122.7 (CTAF) 1

3000
(19.6)

HUUTA
(RNAV 1-GPS REQD)

MSA BR 25 NM
3100

ADF REQUIRED

BRNRD
(RNAV 1-GPS REQD)

18°
298°
BRNRD

LOCALIZER 109.9
I-BRD

LOM/IAF
LAREW
251 BR

051°
1 min
231°
x (CFCID)

1429
3000
358°
(6.6)

R-4301

2100
3000
BR

BR LOM
2976

One Minute Holding Pattern

051°
231°
3000

GS 3.00°
TCH 50

5.3 NM

ELEV 1232		TDZE 1224													
9L (4) 231° 7100 X 150 (5) 6512 X 150 (2) 34 (3) 5 (2) ☆ (H) HIRL Rwy 5-23 and 16-34 1 REIL Rwy 5 and 16 1															
FAF to MAP 5.3 NM															
CATEGORY	A	B	C												
S-ILS 23	1424-½ 200 (200-½)														
S-LOC 23	1680-½ 456 (500-½)	1680-¾ 456 (500-1)	1680-1 456 (500-1)												
CIRCLING	1760-1 528 (600-1)	1760-1½ 528 (600-1½)	1860-2 628 (700-2)												
<table><tr><td>Knots</td><td>60</td><td>90</td><td>120</td><td>150</td><td>180</td></tr><tr><td>Min:Sec</td><td>5:18</td><td>3:32</td><td>2:39</td><td>2:07</td><td>1:46</td></tr></table>				Knots	60	90	120	150	180	Min:Sec	5:18	3:32	2:39	2:07	1:46
Knots	60	90	120	150	180										
Min:Sec	5:18	3:32	2:39	2:07	1:46										

BRainerd, Minnesota

Amdt 7A 29MAR18

46°24'N-94°08'W

BRainerd Lakes RGNL (BRD)

ILS or LOC RWY 23

NC-1, 30 OCT 2025 to 27 NOV 2025

NC-1, 30 OCT 2025 to 27 NOV 2025