

OZARK EIGHT DEPARTURE

AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)
CAHOKIA/ST. LOUIS, ILLINOIS

EC-3, 30 OCT 2025 to 27 NOV 2025

ATIS
121.45
CLNC DEL
118.275
121.8 (when tower closed)
GND CON
121.8
DOWNTOWN TOWER *
119.925 379.3
ST LOUIS DEP CON
123.7 371.875



HAILLSVILLE
114.2 HLV
Chan 89

8000
*2500
281°
(46)

V4

R-095



CABIT


8000
*2100
281°
(32)

NOTE: DME and RADAR required.

V4

ST. LOUIS
117.4 STL
Chan 121

TAKEOFF MINIMUMS
Rwys 12L/R, 23, 30R: Standard.
Rwy 5: 200-1¼ or standard with minimum climb of 343' per NM to 700'.
Rwy 30L: 400-2½ or standard with minimum climb of 220' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2100' prior to DER.



(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

EC-3, 30 OCT 2025 to 27 NOV 2025